

Based on the highly successful ST900 family of Siemens high performance traffic controllers, the ST750SE is a very cost-effective solution to the efficient control of small intersections. Despite its small size, the ST750SE provides the full range of control and signal sequence options found within the ST900 family, and is fully compatible with the Siemens SCOOT UTC, DUSC and Remote Monitoring systems.

Variety of construction options

Recognising the need for installation flexibility, the ST750SE provides two alternative housing solutions:

- **Standard outercase:**

A highly space-efficient enclosure accommodating a range of additional equipment such as integral OTUs, OMUs and loop detector cards.

- **Universal upgrade module:**

A self-contained module, containing all essential controller electronics within a single unit. This option allows the controller to be installed in existing cabinets, providing a particularly cost-effective route to intersection modernisation, as well as in custom enclosures to meet specific customer demand.

Enhanced safety features

Two independent microprocessors and comprehensive hardware 'self-check' features provide exceptional levels of controller safety. Safety is further enhanced by full equivalence-monitoring on all aspect drives (red, amber, green), ensuring that incorrect display of any signal colour is prevented.

The controller's response to fault conditions is programmable and may be set to either safely switch the signals off, or to enter a hardware controlled fail flash mode. This offers selectable 'off' or flash red/yellow for each phase, with programmable mark/space and flash rate.



- Sophisticated traffic control features, ideal for small intersections in the international market
- Dual processor safety system - all colour outputs checked for incorrect operation
- Inbuilt hardware fail flash facilities
- Very small cabinet footprint minimising impact on pedestrian footway
- Easy configuration using Windows-based data generation package (IC4) with optional emulator
- Extensive self-test facility for rapid system validation
- Optional lamp monitoring of all phases and signal colours including wait lamps
- Optional signal dimming for night time operation

ST750SE intersection controller

Traffic Solutions

SIEMENS

User configurable

ST750SE configuration data sets are prepared using the highly acclaimed and easy to use IC4 configurator, with data being directly downloaded into the controller via the handset port.

The configuration process is further simplified by the provision of prepared 'read only' default files which may be modified to adjust all site-dependent variables prior to downloading, minimising the need for on-street changes. Where required however, specific timings and other parameters such as detector allocations and SDE parameters may be adjusted on site using a standard controller handset. The use of an on-street configuration option allows a wider range of parameters, such as phase and stage allocations, to also be modified using the handset.

The optional emulator is a feature-rich tool, which links seamlessly with IC4 to provide an advanced environment for debugging and proving ST750 and ST900 family configurations. Using the same software source files as the controller firmware, it ensures a highly accurate representation of the controller operation on a PC.

Technical specification

Modes of operation

Manual, Vehicle Actuated, Pedestrian Fixed Vehicle Period, Urban Traffic Control, Bus/Light Rail Transit, Part-Time, Fixed-Time, Cableless Linking, Pedestrian Vehicle Actuated, Hurry Call, Emergency Priority

Phases and stages

- No. of hardware phases: 1-6
- No. of software phases: 0-32
- Programmable phase sequences
- 6 independent streams
- 32 stages
- 8 max. green time sets
- 120 phase delays
- 8 call timers
- 8 cancel timers
- 7 all red extension units
- 8 hurry calls
- 8 emergency/priority units

High-speed vehicle detection

Speed discriminations and speed assessment built in 16 assessors

Cableless linking facilities

- 16 plans
- Operating temperature range: -25°C to +65°C

Dimensions

- Standard outercase:
1170mm (H) x 465mm (W) x 370mm (D)

For further information, please contact:

Siemens Mobility, Traffic Solutions, Sopers Lane,
Poole, Dorset BH17 7ER UK

Telephone: +44 (0) 1202 782000

E-mail: sales.stc@siemens.com

www.siemenstraffic.com

© Siemens plc 2010. All rights reserved.

This publication is issued to provide outline information only, which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or service concerned. The Company reserves the right to alter without notice this specification, design, price or conditions of supply of any product or service.